

StayFlat® Sheet Pans



StayFlat® Sheet Pans have sidewalls that are continuously reinforced with an engineered rib that increases its sidewall strength up to 30%. This feature coupled with a concave bottom and residual tensile stress results in a pan that resists bowing and stays flat longer!

Reinforced Sides Prevent Flaring

StayFlat Sheet Pans feature sidewalls that are continuously reinforced with a horizontal engineered rib. This feature increases sidewall strength up to 30% and provides an easy visual identification reference for situations where stronger, flatter sheet pans are required, such as for transport or for baking pies and cakes.

Increased Tensile Strength

A proprietary manufacturing method imparts a residual tensile stress in the StayFlat pan bottom, which further increases the strength of the pan and resists damage from denting or bowing.



Continuously reinforced sidewalls




Concave Bottom Resists Bowing

The method used to increase tensile strength of the StayFlat pan bottom also creates a slightly concave bottom that flattens during heating for even heat distribution and increased resistance to bowing.



NSF StayFlat® Sheet Pan with DuraShield® coating

BUNDY BAKING SOLUTIONS:

-  Baking Pans
-  Pan Coatings & Refurbishment
-  Equipment & Services

Ultimate Coatings

AMERICOAT® ePlus Silicone Glaze

- Longer-lasting performance
- Reduced pan oil and labor costs
- Increased durability
- Reduced food staining


DuraShield® Non-Stick Coating

- Virtually eliminates the use of oils
- Outstanding release characteristics
- Certified to be PFOA-free
- Easy to clean and dishwasher safe

Pan Glo® Recoating Services

Your pans can be cleaned, recoated, and returned to your operation. For more information, call 1.800.652.2151 or visit our website at panglo.com.

Continued on reverse.

 Made in USA with Global Materials



StayFlat® Full-Size Sheet Pans Aluminum

Item #	In Stock	Coating	Description	Overall Size (in)
40694		Plain	16 gauge, wire in rim	17 ⁷ / ₈ x 25 ¹³ / ₁₆ x 1
40698		Glazed	16 gauge, wire in rim	17 ⁷ / ₈ x 25 ¹³ / ₁₆ x 1
40804		Plain	18 gauge, wire in rim	17 ⁷ / ₈ x 25 ¹³ / ₁₆ x 1
40808		Glazed	18 gauge, wire in rim	17 ⁷ / ₈ x 25 ¹³ / ₁₆ x 1
40904		Plain	20 gauge, wire in rim	17 ⁷ / ₈ x 25 ¹³ / ₁₆ x 1
40908		Glazed	20 gauge, wire in rim	17 ⁷ / ₈ x 25 ¹³ / ₁₆ x 1
44690		Glazed	16 gauge, .081" diameter bottom perforation, wire in rim	17 ⁷ / ₈ x 25 ¹³ / ₁₆ x 1
44693		Plain	16 gauge hardcoat anodized aluminum, wire in rim, BÄKALON	17 ⁷ / ₈ x 25 ¹³ / ₁₆ x 1 ¹ / ₁₆
44694		Pre-Seasoned	16 gauge hardcoat anodized aluminum, wire in rim, BÄKALON	17 ⁷ / ₈ x 25 ¹³ / ₁₆ x 1 ¹ / ₁₆
44699		Plain	16 gauge, .081" diameter bottom perforation, wire in rim	17 ⁷ / ₈ x 25 ¹³ / ₁₆ x 1
44891		Plain	18 gauge, .125" diameter bottom perforation, wire in rim	17 ⁷ / ₈ x 25 ¹³ / ₁₆ x 1
44896		Glazed	18 gauge, .125" diameter bottom perforation, wire in rim	17 ⁷ / ₈ x 25 ¹³ / ₁₆ x 1
50691		DuraShield	16 gauge, wire in rim	17 ⁷ / ₈ x 25 ¹³ / ₁₆ x 1
50801		DuraShield	18 gauge, wire in rim	17 ⁷ / ₈ x 25 ¹³ / ₁₆ x 1

In Stock in USA | In Stock in Canada | In Stock in USA & Canada | StayFlat® U.S. Patent No. 9,737,171

Find your local Chicago Metallic sales representative at cmbakeware.com/local-rep for more information or to place an order.

